

mody

ELECTRIC SUBMERSIBLE DRAINAGE PUMP

M-900 SERIES

**PORTABLE ELECTRIC
SUBMERSIBLE PUMP FOR
CORROSIVE & ABRASIVE
APPLICATIONS**

.....

Model M-902T

8" NPT or Hose
35 HP (26kW)
(High Volume - Low Head)

.....

Model M-906T

6" NPT or Hose
35 HP (26kW)
(Low Volume - High Head)

.....



M-900 DESIGN ADVANTAGES

- Stainless Steel Strainer, Shaft, Impeller, Outlet and Hardware for maximum corrosion resistance.
- Choice of impeller materials:
 - 1) 316 Stainless Steel for sea water and corrosive applications and;
 - 2) Nitride Hardened 410 Stainless Steel for abrasive applications. (Standard)
- Tandem Tungsten Carbide/Tungsten Carbide and Tungsten Carbide/Tungsten Carbide mechanical seals.
- Mechanical Seals in wholly enclosed pressure compensated oil chamber.
- Field adjustable Nitrile Rubber-lined Diffuser/Wear Plate Optimizes efficiency throughout the life of the pump. Polyurethane Diffusers and Wear Plates are available.
- Automatic ON/OFF/ON Thermal Overloads embedded in Stator Winding - requires built-in contactor optional.
- Seal Probe Sensor Option available. Requires external controls.
- 1 meter long SS Sheath protects the power cable in demanding mine applications.
- Equipped with Sacrificial Zinc Anodes for maximum life in a saline fluid environment.




Mody Pumps® Inc.
2166 Zeus Court, Bakersfield, CA 93308. USA
Tel.: (661) 392-7600 • Fax: (661) 392-7601
<http://www.modypump.com>
E-mail: sales@modypump.com

mody


ELECTRIC SUBMERSIBLE DRAINAGE PUMP

M-900 SERIES 35HP (26kW)



PERFORMANCE CURVES

MODEL: M902T/M906T (50/60 Hz)



M-900 SERIES

MATERIALS OF CONSTRUCTION AND ENGINEERING DATA

MOTOR

2-pole induction **continuous rated** motor with squirrel cage rotor.
 Stator insulation class 'H' (180°C)
 Speed : 3400 RPM @ 60 Hz, 2800 RPM @ 50 Hz
 Power Rating : 35HP @ 60 Hz, 26kW @ 50Hz Full Load
 Current FLA: 44 Amps @ 460v. 51 Amps @ 400v.
 Max. temperature of the pump liquid : 104°F/40°C
 Max. start/stop per hour : 15
 Star - Delta Starting Optional

POWER SUPPLY

3 phase, 50/60 Hz, AC Supply. Available in any voltage frequency combination. (380/415/460/575/1000V)

BALL BEARINGS

Single row deep groove upper bearing. Double angular contact lower bearings. The bearings are enclosed with high temperature grease-containing special Anti-corrosion additive.

POWER CABLE

Waterproof/oil proof, rubber-insulated, neoprene-sheathed copper conductor flexible cable, 50ft. (15m) length standard. Type SOOW in North America, EPR in the Middle East and HO7RN in the EU.

SHAFT SEAL

Tandem Tungsten Carbide/Tungsten Carbide and Tungsten Carbide/Tungsten Carbide Mechanical seals wholly enclosed in a pressure compensated oil chamber.

CORROSION RESISTANT

Epoxy coated Steel Outer Casing
 Epoxy coated Aluminum Stator Casing
 Nitrile Rubber- Lined Diffuser/Wear plate.
 Shaft: 431 Stainless Steel
 Hardware: 304 Stainless Steel
 Impeller: Nitride Hardened 410SS to 56HRC is Standard.
 pH Range 5 - 8

STRAINER

304 Stainless Steel with 1-9/16" (25.5mm) X 3/8" (10mm) {M 902}, 3/8" (10mm) Round Holes {M 906}

SUBMERGENCE

Submergence below liquid surface min 5" (127mm) max. 50' (15m).

WEIGHTS (Approx. without cable)

M 902: 525lbs. (239Kg)
 M 906: 540lbs. (245Kg)

Due to continuous product development, specifications are subject to change without notice.

03.10.Rev.0